

## Accessories

### Leak Lock® Joint Sealant Compound

Leak Lock® is a soft setting pipe joint compound for sealing threaded joints, flanged joints, gasket surfaces and mating surfaces. This resin based paste remains permanently flexible, adheres to internal surfaces and fills voids. It is ideal for use on metal and plastic materials subject to extreme vibrations, temperatures from -200°F (-93°C) to 400°F (204°C) full vacuums to 10,000 PSI. Leak Lock seals all refrigerants (R12, R22, R502, R134A, etc.) petroleum products, natural and manufactured gases, steam, water, air, etc.

- ✓ Installation
- ✓ Maintenance
- ✓ Repair



MARS NO.	DESCRIPTION	CASE QTY
93803	1-1/3 oz. Plastic Tube	12
93804	4 oz. Plastic bottle w/brush top	12
93805	16 oz. Plastic jar w/brush top	12
93799	1-1/3 oz. Blister Pack	12

### Leak Lock® Gold Joint Sealant Compound

Leak Lock® GOLD is a soft setting pipe joint compound for sealing threaded joints, flanged joints, gasket surfaces and mating surfaces. This resin based paste remains permanently flexible, adheres to internal surfaces and fills voids. It is ideal for use on metal and plastic materials subject to extreme vibrations, temperatures from -200°F (-93°C) to 400°F (204°C) full vacuums to 10,000 PSI. Leak Lock seals all refrigerants (R12, R22, R502, R134A, etc.) petroleum products, natural and manufactured gases, steam, water, air, etc. Same as Leak Lock. Has PTFE added.

- ✓ Installation
- ✓ Maintenance
- ✓ Repair



MARS NO.	DESCRIPTION	CASE QTY
93798	1-1/3 oz. Plastic Tube	12
93796	4 oz. Plastic bottle w/brush top	12
93795	16 oz. Plastic jar w/brush top	12
93797	1-1/3 oz. Blister Pack	12

### Leak Lock® Advanced Specialty Sealant

Leak Lock® Advanced Specialty Sealant seals small imperfections in various refrigerants and refrigeration lubricant systems, preventing leaks and sealing over 1500 psi of pressure on compression and flare fittings. It is designed for use on Gaskets, O-rings, Flare Fittings, Schrader Valves, and more. It doesn't dry, cleans up easily, and is applicable to many surface types. It's compatible with all refrigerants and refrigeration lubricants and does not contaminate systems. It's resistant to temperature or pressure spikes and equipment vibrations.

- ✓ Installation
- ✓ Maintenance



MARS NO.	DESCRIPTION	CASE QTY
93775	1-1/3 oz. tube Blister Pack	12

### Leak Lock® One-Step PVC Cement

**Replaces Over 12 other Products for Scope and Performance!**

Multi-Purpose One-Step PVC Cement! No primer needed, fast-setting, and perfect for all weather conditions. It works effectively on both wet and dry pipes, including flexible ones. Plus, it allows for immediate pressure testing and meets ASTM D2564 standards.

- ✓ Installation
- ✓ Repair



MARS NO.	DESCRIPTION	CASE QTY
93771	Leak Lock PVC Cement, 4 oz.	12
93770	Leak Lock PVC Cement, 8 oz.	12