OPTIONAL A	ACCESSORIES -	ORDE	RSEPARATELY			
Compressor Low Ambient Cut-Off Switch Compressor Sound Cover Compressor Time-Off Control		45F08	•	•	•	•
		18J42 47J27	•	•	•	•
5/8 in. tubing	50A93	•	•	•	•	
Hail Guards	24 x 24 x 28 in.	14X09	•			
	28 x 28 x 28 in.	14X16		•		
	28 x 28 x 36 in.	14X14			•	
	28 x 28 x 32 in.	14X19				•
Indoor Blower Off Delay Relay		58M81	•	•	•	•
Loss of Charge Switch		84M23	•	•	•	•
⁴ Low Ambient Kit (Fan Cycling) (30°F)		34M72	•	•	•	•
⁴ Low Ambient Control (0°F) 208/230V only	Speed Control	X5867	•	•	•	•
	Weatherproof Kit	56N41	•	•	•	•
Refrigerant Line L15-65-30 Sets		15-65-40, 15-65-50	•	•	•	
	Field I	-abricate				•
Unit Stand-Off Kit 94J45		94J45	•	•	•	•

NOTE - Extremes of operating range are plus 10% and minus 5% of line voltage.







Visit us at www.marsdelivers.com
Contact us at 517-787-2100

NOTE - Due to Allied Commercial ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

¹ Refrigerant charge sufficient for 15 ft. length of refrigerant lines.

² HACR type circuit breaker or fuse.

³ Refer to National or Canadian Electrical Code manual to determine wire, fuse and disconnect size requirements.

⁴ Freezestat is recommended with Low Ambient Control.